

SKU	TIRE SIZE	PR	TT/TL	LSI	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		INFLATING PRESSURE (psi/bar)	LOAD CAPACITY PER TIRE (KG)							
					RECOM. (INCHES)	PERMITTED (INCHES)	Section Width Min-Max	OUTER DIAMETER (MM)	DYNAMIC RADIUS CIRCLE (MM)	STATIC LOADED RADIUS (MM)		Speed (KM/H)							
												10	15	20	25	30	40	50	65
62381	420/85R34		TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	9 / 0.6	1955				1560	1460	1330	
			TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	12 / 0.8	2275				1815	1700	1545	
			TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	15 / 1.0	2595				2070	1935	1765	
			TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	17 / 1.2	2915				2330	2175	1980	
			TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	20 / 1.4	3235				2585	2415	2195	
			TL	142 A8/139 B	W15L	W13-W14L	418	1578	4750	715	23 / 1.6	3555				2840	2650	2430	
61908	14.9-28	8	TT	130 A6	W13	W11, W12	378	1365	4068	618	22 / 1.5	2480	2300	2125	1895	1770	1595		
			TT	130 A6	W13	W11, W12	378	1365	4068	618	23 / 1.6	3730	2610	2240	1995	1865	1680		
			TT	130 A6	W13	W11, W12	378	1365	4068	618	26 / 1.8	3800	2660	2280	2035	1900	1710		
57786	18.4-30	10	TT	145 A6	W16L	W15L	467	1550	4619	697	22 / 1.5	3780	3510	3240	2890	2700	2430		
			TT	145 A6	W16L	W15L	467	1550	4619	697	23 / 1.6	3985	3700	3415	3045	2845	2560		
			TT	145 A6	W16L	W15L	467	1550	4619	697	26 / 1.8	4060	3770	3480	3105	2900	2610		
57787	23.1-30	12	TT	151 A6	DW20B	-	592	1710	5090	770	20 / 1.4	4150	3855	3500	3170	2965	2610		
			TT	151 A6	DW20B	-	592	1710	5090	770	22 / 1.5	4440	4125	3740	3395	3170	2790		
			TT	151 A6	DW20B	-	592	1710	5090	770	25 / 1.7	4830	4485	4070	3690	3450	3035		